EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 175 KONIC EVO



### FEATURES

Intended Use:	Exteriors
Installation:	Floor/Floor
Fixing:	Via pre-drilled holes for hardware (not included)
Body/Structure:	Extruded aluminum body and die-cast aluminum optical compartment
Painting:	Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorzirconing, epoxy powder primer and polyester powder surface finish).
Finish:	Anthracite gray
Reflector/Optics:	Die-cast conical reflector
Glass/Screen:	Transparent glass
Driver:	Integrated driver for LED, 500mA dc stabilized output

### TECHNICAL DATA

Beam:Symmetrical-homnidirectional 360°Current:500mAInsulation class:2Weight:5 kgIP grade:65Grade IK:10Glow wire:850 °CLamp included:YesLED type:SDM LEDOverall power:23 WAppliance flow:885 lmNominal duration:50.000 (h) L90 B50Color temperature:4000 KColor consistency:3 SDCM	Tension:	220-240V 50/60Hz
Insulation class:2Weight:5 kgIP grade:65Grade IK:10Glow wire:850 °CLamp included:YesLED type:SDM LEDOverall power:23 WAppliance flow:885 lmNominal duration:50.000 (h) L90 B50Color temperature:4000 KColor rendering index:>90	Beam:	Symmetrical-homnidirectional 360°
Weight:5 kgIP grade:65Grade IK:10Glow wire:850 °CLamp included:YesLED type:SDM LEDOverall power:23 WAppliance flow:885 lmNominal duration:50.000 (h) L90 B50Color temperature:4000 KColor rendering index:>90	Current:	500mA
IP grade:   65     Grade IK:   10     Glow wire:   850 °C     Lamp included:   Yes     LED type:   SDM LED     Overall power:   23 W     Appliance flow:   885 lm     Nominal duration:   50.000 (h) L90 B50     Color temperature:   4000 K	Insulation class:	2
Grade IK:   10     Glow wire:   850 °C     Lamp included:   Yes     LED type:   SDM LED     Overall power:   23 W     Appliance flow:   885 lm     Nominal duration:   50.000 (h) L90 B50     Color temperature:   4000 K     Color rendering index:   >90	Weight:	5 kg
Glow wire: 850 °C   Lamp included: Yes   LED type: SDM LED   Overall power: 23 W   Appliance flow: 885 lm   Nominal duration: 50.000 (h) L90 B50   Color temperature: 4000 K   Color rendering index: >90	IP grade:	65
Lamp included:   Yes     LED type:   SDM LED     Overall power:   23 W     Appliance flow:   885 lm     Nominal duration:   50.000 (h) L90 B50     Color temperature:   4000 K     Color rendering index:   >90	Grade IK:	10
LED type:SDM LEDOverall power:23 WAppliance flow:885 lmNominal duration:50.000 (h) L90 B50Color temperature:4000 KColor rendering index:>90	Glow wire:	850 °C
Overall power:23 WAppliance flow:885 lmNominal duration:50.000 (h) L90 B50Color temperature:4000 KColor rendering index:>90	Lamp included:	Yes
Appliance flow:885 lmNominal duration:50.000 (h) L90 B50Color temperature:4000 KColor rendering index:>90	LED type:	SDM LED
Nominal duration:50.000 (h) L90 B50Color temperature:4000 KColor rendering index:>90	Overall power:	23 W
Color temperature: 4000 K Color rendering index: >90	Appliance flow:	885 lm
Color rendering index: >90	Nominal duration:	50.000 (h) L90 B50
	Color temperature:	4000 K
Color consistency: 3 SDCM	Color rendering index:	>90
	Color consistency:	3 SDCM

LIGHT SOURCE: 1 x 20W 2652.40Im



Maximum nighttime ambiance temperature when the fitting is on not exceeding 50°C Minimum nighttime ambiance temperature when the fitting is on not lower than -20°C Maximum daytime ambiance temperature when the fitting is off not exceeding 60°C





# VERSO 175 KONIC EVO - H.400mm - Omnidirectional E6026-LBN-N




EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 175 KONIC EVO

## **TECHNICAL DRAWING**

# 

## PHOTOMETRIC CURVES



Area: 15,33 x 21,23

Area: 19,16 x 26,54

a: 23,00 x 31,85

C90-C270: 52,73°+53,27

0

8 m

10 n

12 m

2/0

1/0

1/

-C180: 18,67°+17,20°

## ACCESSORIES



899-N

Formwork for ground fixing

IP68 connector ø 7 to 12mm



646308 NE

646308

646636 NE

IP68 "T" connector ø7 to 10mm for continuous rows



# VERSO 175 KONIC EVO - H.400mm - Omnidirectional E6026-LBN-N

EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 175 KONIC EVO



 Galvanized steel fixing plate with anchor belts

4074-N

## COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using highquality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

