

## FEATURES

Intended Use:	Exteriors
Installation:	Wall Recessed
Recessed hole:	Recessed formwork type 503
Fixing:	Fastening system with hardware
Body/Structure:	Die-cast aluminum body EN AB-47100
Painting:	Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorozirconing, epoxy powder primer and polyester powder surface finish).
Finish:	Grey
Reflector/Optics:	LED lens in methacrylate
Driver:	Integrated driver for LED, 500mA dc stabilized output

## TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Asymmetrical
Insulation class:	2
Weight:	1 kg
IP grade:	68
Glow wire:	850 °C
Lamp included:	Yes
LED type:	Power LED
Overall power:	2 W
Appliance flow:	71 lm
Nominal duration:	50000 (h) L80 B10
Color temperature:	6000 K
Color rendering index:	>80
Color consistency:	4 SDCM

LIGHT SOURCE: 1 x LED 2.00W 165lm




## NOTES

ip grade referred to the light fixture only; power supply ip 67

Maximum nighttime ambient temperature when the fitting is on not exceeding 50°C  
Minimum nighttime ambient temperature when the fitting is on not lower than -20°C  
Maximum daytime ambient temperature when the fitting is off not exceeding 60°C

**TECHNICAL DRAWING**



**COMPANY**

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.