



## FEATURES

Intended Use:	Exteriors
Installation:	Wall Mounting
Fixing:	Fastening system with hardware
Body/Structure:	Steel frame and thermoplastic plate
Finish:	White
Reflector/Optics:	99.8% pure aluminum reflector
Driver:	Driver integrated in the LED module

## TECHNICAL DATA

Tension:	230-240V 50/60Hz
Beam:	Asymmetrical
Insulation class:	2
Weight:	0.16 kg
IP grade:	65
Glow wire:	850 °C
Lamp included:	Yes
LED type:	SMD LED
Overall power:	2 W
Appliance flow:	150 lm
Nominal duration:	30.000 (h) L80 B20
Color temperature:	4000 K
Color rendering index:	>80
Color consistency:	3 SDCM

LIGHT SOURCE: 1 x LED 1.00W 150lm




## NOTES



On request: body coloring BLACK, GREY, RAL

Maximum nighttime ambient temperature when the fitting is on not exceeding 50°C  
 Minimum nighttime ambient temperature when the fitting is on not lower than -20°C  
 Maximum daytime ambient temperature when the fitting is off not exceeding 60°C

**TECHNICAL DRAWING**



**PHOTOMETRIC CURVES**



**COMPANY**

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.