





FEATURES

Intended Use:	Foodlighting,Interior
Installation:	Suspension
Fixing:	Suspension system with steel rope(s) L=3100 mm and micrometric adjustment
Body/Structure:	Aluminum sheet metal body and aluminum die-cast optical compartment EN AB-47100.
Painting:	Interior polyester powder coating
Finish:	Black
Reflector/Optics:	99.8% pure aluminum reflector
Glass/Screen:	Clear tempered glass
Driver:	Integrated power supply for LED, stabilized output 1050mA dc

TECHNICAL DATA

Beam: Symmetrical diffusing 30° Current: 1050mA Insulation class: 1 Weight: 3.10 kg IP grade: 20 Glow wire: 850 °C Lamp included: Yes LED type: COB LED Overall power: 37 W Appliance flow: 2436 lm Nominal duration: 50000 Color temperature: K	Tension:	220-240V 50/60Hz
Insulation class: Weight: 3.10 kg IP grade: 20 Glow wire: 850 °C Lamp included: Yes LED type: C0B LED Overall power: 37 W Appliance flow: 2436 lm Nominal duration: 50000	Beam:	Symmetrical diffusing 30°
Weight: 3.10 kg IP grade: 20 Glow wire: 850 °C Lamp included: Yes LED type: C0B LED Overall power: 37 W Appliance flow: 2436 lm Nominal duration: 50000	Current:	1050mA
IP grade: 20 Glow wire: 850 °C Lamp included: Yes LED type: COB LED Overall power: 37 W Appliance flow: 2436 lm Nominal duration: 50000	Insulation class:	1
Glow wire: 850 °C Lamp included: Yes LED type: C0B LED Overall power: 37 W Appliance flow: 2436 lm Nominal duration: 50000	Weight:	3.10 kg
Lamp included: Yes LED type: C0B LED Overall power: 37 W Appliance flow: 2436 lm Nominal duration: 50000	IP grade:	20
LED type: COB LED Overall power: 37 W Appliance flow: 2436 lm Nominal duration: 50000	Glow wire:	850 °C
Overall power: 37 W Appliance flow: 2436 lm Nominal duration: 50000	Lamp included:	Yes
Appliance flow: 2436 lm Nominal duration: 50000	LED type:	COB LED
Nominal duration: 50000	Overall power:	37 W
	Appliance flow:	2436 lm
Color temperature: K	Nominal duration:	50000
	Color temperature:	K
Color rendering index: >90	Color rendering index:	>90
Color consistency: 3 SDCM	Color consistency:	3 SDCM

LIGHT SOURCE: 1 x LED 37.00W 2730lm












NOTES

suitable for cold cuts. Optional: Fabric power cord in two different colors: cod.643000 (WHITE) cod.613750 (BLACK)





FOODLIGHTING > FOOD SUSPENSIONS > AURORA FOOD

TECHNICAL DRAWING



PHOTOMETRIC CURVES





COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

