




FEATURES

Intended Use:	Indoor,outdoor,SIDESIGN
Installation:	Walls
Body/Structure:	Body made of painted sheet steel
Painting:	Galvanic treatment
Finish:	Brown
Reflector/Optics:	Methacrylate led lens
Glass/Screen:	Stainless steel/painted front screen
Driver:	Integrated into the device

TECHNICAL DATA


Tension:	220/240v, 24 V dc
Beam:	Direct light
Insulation class:	2
Weight:	3.50 kg
IP grade:	IP40
Grade IK:	10
Glow wire:	850° °C
Lamp included:	Yes
LED type:	SMD LED
Overall power:	13 W
Appliance flow:	1820 lm
Nominal duration:	50.000 ore L80 B31
Color temperature:	3000 K
Color rendering index:	>90
Color consistency:	3 SDCM



NOTES

equipment: recessed box 506l

TECHNICAL DRAWING



COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.