VERSO 90 - H.900mm - Omnidirectional E5912-LBC

EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 90



FEATURES

Intended Use:	Exteriors
Installation:	Floor/Floor
Body/Structure:	Extruded aluminum body and die-cast aluminum optical compartment
Painting:	Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorzirconing, epoxy powder primer and polyester powder surface finish).
Finish:	Anthracite
Reflector/Optics:	99.8% pure aluminum reflector
Glass/Screen:	UV-stabilized transparent polycarbonate
Driver:	Integrated driver for LED, 500mA dc stabilized output

TECHNICAL DATA

Beam:Symmetrical, omnidirectional 360°Current:500mAInsulation class:2Weight:2.4 kgIP grade:65Grade IK:10Glow wire:850 °CLamp included:YesLED type:SMD LEDOverall power:13 WAppliance flow:870 lm
Insulation class:2Weight:24 kgIP grade:65Grade IK:10Glow wire:850 °CLamp included:YesLED type:SMD LEDOverall power:13 W
Weight: 24 kg IP grade: 65 Grade IK: 10 Glow wire: 850 °C Lamp included: Yes LED type: SMD LED Overall power: 13 W
IP grade: 65 Grade IK: 10 Glow wire: 850 °C Lamp included: Yes LED type: SMD LED Overall power: 13 W
Grade IK:10Glow wire:850 °CLamp included:YesLED type:SMD LEDOverall power:13 W
Glow wire: 850 °C Lamp included: Yes LED type: SMD LED Overall power: 13 W
Lamp included: Yes LED type: SMD LED Overall power: 13 W
LED type: SMD LED Overall power: 13 W
Overall power: 13 W
Appliance flow: 870 lm
Nominal duration: 50000 (h) L90 B50
Color temperature: 3000 K
Color rendering index: >90
Color consistency: 3 SDCM

LIGHT SOURCE: 1 x LED 11.00W 1448Im



Maximum nighttime ambiance temperature when the fitting is on not exceeding 50°C Minimum nighttime ambiance temperature when the fitting is on not lower than -20°C Maximum daytime ambiance temperature when the fitting is off not exceeding 60°C





VERSO 90 - H.900mm - Omnidirectional E5912-LBC





EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 90

TECHNICAL DRAWING



PHOTOMETRIC CURVES






ACCESSORIES



3127

Ring for base cover 160mm



 Galvanized steel pull plate

4073





VERSO 90 - H.900mm - Omnidirectional E5912-LBC

EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 90



IP68 connector ø 7 to 12mm



646308 NE



646636 NE

IP68 "T" connector ø 7 to 10mm for continuous rows

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using highquality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

