




FEATURES

Intended Use:	Exteriors
Installation:	Ground Recessed
Body/Structure:	Stainless steel body and ring/frame - Thermoplastic material formwork
Finish:	Satin stainless steel
Reflector/Optics:	LED lens in methacrylate
Glass/Screen:	Clear screen-printed tempered glass
Driver:	Not included; must be ordered separately

TECHNICAL DATA

Beam:	Symmetrical diffusing 100°
Current:	350mA
Insulation class:	3
Weight:	0.3 kg
IP grade:	67
Grade IK:	7
Drive-over:	Yes
Static load:	500 kg
Glass temperature:	50 °C
Glow wire:	850 °C
Lamp included:	Yes
LED type:	Power LED
Overall power:	3 W
Color temperature:	RGB
Color rendering index:	>80
Color consistency:	3 SDCM

LIGHT SOURCE: 1 x LED RGB 3.00W 0lm



NOTES

Optional: ...-TSC TORX security screws


On request: EM

Maximum nighttime ambient temperature when the fitting is on not exceeding 50°C

Minimum nighttime ambient temperature when the fitting is on not lower than -20°C

Maximum daytime ambient temperature when the fitting is off not exceeding 60°C


TECHNICAL DRAWING



DRIVER

646372-1

Driver KIT RGB 21W IP20 350mA



ACCESSORIES


IP68 connector \varnothing 7 to 12mm



646308

NE

Recessed box



185

NE

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.