



## FEATURES

Intended Use:	Exteriors
Installation:	Recessed Ceiling
Recessed hole:	Ø 73 mm
Fixing:	Steel springs
Body/Structure:	EN AB-47100 aluminum die-cast body and ABS ring/frame
Painting:	Luminaire body base painted in polyester powder with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorzirconating, epoxy powder primer and polyester powder surface finish).
Finish:	White
Reflector/Optics:	Metalized polycarbonate mirror reflector
Glass/Screen:	Clear tempered glass
Driver:	Not included must be ordered separately

## TECHNICAL DATA

Beam:	Symmetrical
Weight:	0.35 kg
IP grade:	67
Drive-over:	Yes
Glow wire:	850 °C



**Gli apparecchi non sono muniti di lampada**  
**Fittings are not equipped with bulb**




## NOTES

Only for led source: special version prepared for formwork suitable for concrete installations.

ordering example: E8140C-MLBC-10 (add the c after the item number and complete the code) + order formwork item 148.

Maximum nighttime ambient temperature when the fitting is on not exceeding 50°C  
Minimum nighttime ambient temperature when the fitting is on not lower than -20°C  
Maximum daytime ambient temperature when the fitting is off not exceeding 60°C

## TECHNICAL DRAWING



## COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.