



FEATURES

Intended Use:	Exteriors
Installation:	Ground Recessed
Body/Structure:	Body made of extruded aluminum - Frame/Ring and wall formwork made of stainless steel.
Painting:	Anodized
Finish:	Satin stainless steel
Reflector/Optics:	99.8% pure aluminum reflector
Glass/Screen:	Tempered frosted glass
Driver:	LED driver, 12Vdc output

TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Concentric symmetrical 20°
Insulation class:	3
Weight:	1.90 kg
IP grade:	67
Grade IK:	7
Drive-over:	Yes
Static load:	500 kg
Glass temperature:	35 °C
Glow wire:	650 °C
Lamp included:	Yes
LED type:	SMD LED
Overall power:	4 W
Nominal duration:	50.000 (h) L90 B20
Color temperature:	3000 K
Color rendering index:	>70
Color consistency:	5 SDCM

LIGHT SOURCE: 1 x LED 24.00W 1400lm



NOTES


On request: 1 m length.

RECESSED VERSION FOR COUNTERFITTINGS (10 mm thick)
Length 390 mm with groove 30 x 370 mm



IP 20 Remote driver supplied
IP 67 On request code 645367

Maximum nighttime ambience temperature when the fitting is on not exceeding 50°C
Minimum nighttime ambience temperature when the fitting is on not lower than -20°C
Maximum daytime ambience temperature when the fitting is off not exceeding 60°C

TECHNICAL DRAWING



PHOTOMETRIC CURVES



COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.