AURORA XS 5403-LBC-30



INDOOR > WALL - CEILING - SUSPENSION > AURORA





FEATURES

Interior
Suspension
Suspension system with steel rope(s) L=3100 mm and micrometric adjustment
Aluminum sheet metal body and aluminum die-cast optical compartment EN AB-47100.
Interior polyester powder coating
Grey
99.8% pure aluminum reflector
Clear tempered glass
Integrated power supply for LED, stabilized output 1050mA dc

TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Symmetrical diffusing 30°
Current:	1050mA
Insulation class:	1
Weight:	2.2 kg
IP grade:	20
Glow wire:	850 °C
Lamp included:	Yes
LED type:	COB LED
Overall power:	41 W
Appliance flow:	4730 lm
Nominal duration:	50.000 (h)
Color temperature:	3000 K
Color rendering index:	>90
Color consistency:	3 SDCM

LIGHT SOURCE: 1 x LED 37.00W 5300Im



NOTES

On request: sitrack track adapter On request: led with 2700k color temperature. On request: fabric power cord in two different colors: cod.643000 (WHITE) cod.613750 (BLACK)

AURORA XS 5403-LBC-30





INDOOR > WALL - CEILING - SUSPENSION > AURORA

TECHNICAL DRAWING



PHOTOMETRIC CURVES





ACCESSORIES

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using highquality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

