D2218-MLBC40S

INDOOR > WALL - CEILING - SUSPENSION > DROP 30S





FEATURES

Intended Use:	Interior
Installation:	Suspension
Fixing:	Suspension system by supply cable 2x0.75mm2 - L = 2000mm
Body/Structure:	Extruded aluminum body
Painting:	Interior polyester powder coating
Finish:	Grey
Reflector/Optics:	PMMA LED Lens
Driver:	Integrated driver for LED, 200mA dc stabilized output

TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Symmetrical diffusing 40°
Current:	200mA
Insulation class:	2
Weight:	0.68 kg
IP grade:	20
Glow wire:	650 °C
Lamp included:	Yes
LED type:	COB LED
Overall power:	8.3 W
Appliance flow:	777 lm
Nominal duration:	50.000(h) L900 B20
Color temperature:	3000 K
Color rendering index:	>90
Color consistency:	3 SDCM

LIGHT SOURCE: 1 x LED 7.30W 777Im















NOTES

H= 300 mm

Optional: Fabric power cord in two different colors: cod.643000 (WHITE) cod.613750 (BLACK)





INDOOR > WALL - CEILING - SUSPENSION > DROP 30S

TECHNICAL DRAWING



PHOTOMETRIC CURVES





COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

