# E4902-LBN-M



EXTERIOR > CEILING/WALL LIGHTS > MINI MONO TONDO



## **FEATURES**

Intended Use:	Exteriors
Installation:	Wall Mounting
Body/Structure:	Die-cast aluminum body EN AB-47100 - Stainless steel ring.
Painting:	Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorzirconing, epoxy powder primer and polyester powder surface finish).
Finish:	Grey
Reflector/Optics:	99.8% pure aluminum reflector
Glass/Screen:	Clear tempered glass
Driver:	Integrated driver for LED, 350mA dc stabilized output

## **TECHNICAL DATA**

220-240V 50/60Hz
Symmetrical diffusing 40°
350mA
2
2.9 kg
65
07
850 °C
Yes
COB LED
13.5 W
1293 lm
50.000 (h) L80 B20
4000 K
>90
3 SDCM
B1-U0-G0
93-98-99-100-100

LIGHT SOURCE: 1 x LED 11.50W 2000Im














### **NOTES**

Maximum nighttime ambiance temperature when the fitting is on not exceeding  $50^{\circ}$ C Minimum nighttime ambiance temperature when the fitting is on not lower than -20°C Maximum daytime ambiance temperature when the fitting is off not exceeding  $60^{\circ}$ C





EXTERIOR > CEILING/WALL LIGHTS > MINI MONO TONDO

# **TECHNICAL DRAWING**



### PHOTOMETRIC CURVES





## **COMPANY**

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

