STARGATE 950 ECO - Direct-indirect light 5611-LBC-DIM3

INDOOR > WALL - CEILING - SUSPENSION > STARGATE







FEATURES

Intended Use:	Interior
Installation:	Suspension
Fixing:	Suspension system with steel rope(s) L=3100 mm and micrometric adjustment
Body/Structure:	Sheet steel body
Painting:	Interior polyester powder coating
Finish:	Black
Glass/Screen:	Bi-satin polycarbonate diffuser screen
Driver:	Remote dimmable 1-10V power supply for LED

TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Symmetrical, dual emission
Current:	650mA
Insulation class:	1
Weight:	10.3 kg
IP grade:	40
Glow wire:	850 °C
Lamp included:	Yes
LED type:	Power LED
Overall power:	93.4 W
Appliance flow:	7770 lm
Nominal duration:	50.000 ore L80 B20
Color temperature:	3000 K
Color rendering index:	>80
Color consistency:	3 SDCM

LIGHT SOURCE: 24 x LED 3.60W 540Im



NOTES


Optional: Fabric power cord in two different colors: cod.643000 (WHITE) cod.613750 (BLACK)




STARGATE 950 ECO - Direct-indirect light 5611-LBC-DIM3


INDOOR > WALL - CEILING - SUSPENSION > STARGATE

TECHNICAL DRAWING



PHOTOMETRIC CURVES





COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using highquality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.



