



FEATURES

Intended Use:	Exteriors,SIDESIGN
Installation:	Floor/wall/plafone fixing
Body/Structure:	Stainless steel body
Finish:	Satin stainless steel
Reflector/Optics:	LED lens in methacrylate
Glass/Screen:	Clear tempered glass

TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Concentric symmetrical 10°
Current:	700mA Vdc
Insulation class:	3
Weight:	0.3 kg
IP grade:	68
Glow wire:	850° °C
Lamp included:	Yes
LED type:	Power LED
Overall power:	02.50 W
Appliance flow:	170 lm
Nominal duration:	50.000 (h) L80 B10
Color temperature:	3000K K
Color rendering index:	80
Color consistency:	4 SDCM


LIGHT SOURCE: 1 x LED 2.50W 170lm



NOTES

Maximum room temperature at night when the appliance is turned on not exceeding 50°C
Minimum room temperature at night when the appliance is turned on not less than -20°C
Maximum ambient daytime temperature with the appliance off not exceeding 60°C

TECHNICAL DRAWING



ACCESSORIES



Spike to be buried

E8007
3162



316 stainless steel braided sleeving L:500mm

3162

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.