

FEATURES

Intended Use:	Exteriors
Installation:	Ground recessed
Body/Structure:	33mm diameter oxidized aluminum body, silicone seals. AISI 316 polished stainless steel ring.
Finish:	Polished stainless steel
Glass/Screen:	Toughened safety glass
Driver:	Not included; must be ordered separately

TECHNICAL DATA

Beam:	Symmetrical Concentrated 10°
Current:	700mA
Insulation class:	3
Weight:	013 kg
IP grade:	68
Drive-over:	Yes
Glow wire:	850 °C
Lamp included:	Yes
LED type:	Led di potenza 2.2W
Overall power:	2.2 W
Appliance flow:	230 lm
Nominal duration:	50.000 (h) L90 B20
Color temperature:	4000 K
Color rendering index:	>80
Color consistency:	3 SDCM




NOTES


Supplied complete with outdoor power cable 2x0.5mmq useful length 250mm. Supplied complete with D.40mm polyethylene installation formwork.

Maximum nighttime ambience temperature when the fitting is on not exceeding 50°C
Minimum nighttime ambience temperature when the fitting is on not lower than -20°C
Maximum daytime ambience temperature when the fitting is off not exceeding 60°C

TECHNICAL DRAWING



DRIVER



646364
DRIVER
DRIVER ON-OFF14W 350mA IP 67

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.