VERSO 90 - H.600mm - One-way E5906-LBN

EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 90



FEATURES

| Intended Use: | Exteriors |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Installation: | Floor/Floor |
| Body/Structure: | Extruded aluminum body and die-cast aluminum optical compartment |
| Painting: | Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorzirconing, epoxy powder primer and polyester powder surface finish). |
| Finish: | Black |
| Reflector/Optics: | 99.8% pure aluminum reflector |
| Glass/Screen: | UV-stabilized transparent polycarbonate |
| Driver: | Integrated driver for LED, 500mA dc stabilized output |

TECHNICAL DATA

| Tension: | 220-240V 50/60Hz |
|------------------------|-----------------------------------|
| Beam: | Symmetrical, single emission 180° |
| Current: | 500mA |
| Insulation class: | 2 |
| Weight: | 1.8 kg |
| IP grade: | 65 |
| Grade IK: | 10 |
| Glow wire: | 850 °C |
| Lamp included: | Yes |
| LED type: | SMD LED |
| Overall power: | 13 W |
| Appliance flow: | 480 lm |
| Nominal duration: | 50.000 (h) L90 B50 |
| Color temperature: | 4000 K |
| Color rendering index: | >90 |
| Color consistency: | 3 SDCM |

LIGHT SOURCE: 1 x LED 11.00W 1560Im



Maximum nighttime ambiance temperature when the fitting is on not exceeding 50°C Minimum nighttime ambiance temperature when the fitting is on not lower than -20°C Maximum daytime ambiance temperature when the fitting is off not exceeding 60° C






VERSO 90 - H.600mm - One-way E5906-LBN


EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 90

TECHNICAL DRAWING



PHOTOMETRIC CURVES





ACCESSORIES



Ring for base cover 160mm



Formwork for ground fixing

894



Galvanized steel pull plate

4073







VERSO 90 - H.600mm - One-way E5906-LBN

EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 90



IP68 connector ø 7 to 12mm



646308 NE



646636 NE

IP68 "T" connector ø 7 to 10mm for continuous rows

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using highquality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

