

FEATURES

Intended Use:	Exteriors
Installation:	Wall Mounting
Body/Structure:	Die-cast aluminum body EN AB-47100
Painting:	Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorozirconing, epoxy powder primer and polyester powder surface finish).
Finish:	Grey
Glass/Screen:	Opal polycarbonate diffuser screen

TECHNICAL DATA

Tension:	230V
Beam:	Symmetrical, single emission
Current:	400mA
Insulation class:	1
Weight:	1.9 kg
IP grade:	65
Glow wire:	850 °C
Lamp included:	Yes
LED type:	Power LED
Overall power:	23 W
Appliance flow:	910 lm
Nominal duration:	50.000
Color temperature:	3000 K
Color rendering index:	>90
Color consistency:	3 SDCM
Bug Evaluation:	B0-U0-G0
CEN flow code:	48-79-96-100-100


LIGHT SOURCE: 1 x 20W 1698lm





NOTES

Maximum nighttime ambiance temperature when the fitting is on not exceeding 50°C
 Minimum nighttime ambiance temperature when the fitting is on not lower than -20°C
 Maximum daytime ambiance temperature when the fitting is off not exceeding 60°C

TECHNICAL DRAWING



PHOTOMETRIC CURVES



COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.