5536N-LBN-DA

INDOOR > WALL - CEILING - SUSPENSION > BIG NEW





FEATURES

Intended Use:	Interior
Installation:	Wall, ceiling
Body/Structure:	Aluminum Led fixing disk and heat sink, internal structure of pre-galvanized sheet steel.
Painting:	Interior polyester powder coating
Finish:	Black
Glass/Screen:	Bi-frosted methacrylate diffuser screen
Driver:	Built-in DALI dimmable driver for LED, max output 700mA dc

TECHNICAL DATA

Beam: Symmetrical diffusing Current: 700mA Insulation class: 1 Weight: 7.30 kg IP grade: 40 Glow wire: 650 °C Lamp included: Yes Overall power: 55 W Appliance flow: 5538 lm Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color consistency: 3 SDCM	Tension:	220/240v
Insulation class: Weight: 7.30 kg IP grade: 40 Glow wire: 650 °C Lamp included: Yes Overall power: 55 W Appliance flow: 5538 lm Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color rendering index: >90	Beam:	Symmetrical diffusing
Weight: 7.30 kg IP grade: 40 Glow wire: 650 °C Lamp included: Yes Overall power: 55 W Appliance flow: 5538 lm Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color rendering index: >90	Current:	700mA
IP grade: 40 Glow wire: 650 °C Lamp included: Yes Overall power: 55 W Appliance flow: 5538 Im Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color rendering index: >90	Insulation class:	1
Glow wire: 650 °C Lamp included: Yes Overall power: 55 W Appliance flow: 5538 Im Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color rendering index: >90	Weight:	7.30 kg
Lamp included: Yes Overall power: 55 W Appliance flow: 5538 lm Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color rendering index: >90	IP grade:	40
Overall power: 55 W Appliance flow: 5538 lm Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color rendering index: >90	Glow wire:	650 ℃
Appliance flow: 5538 lm Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color rendering index: >90	Lamp included:	Yes
Nominal duration: 50.000(h) L80 B20 Color temperature: 4000 K Color rendering index: >90	Overall power:	55 W
Color rendering index: >90	Appliance flow:	5538 lm
Color rendering index: >90	Nominal duration:	50.000(h) L80 B20
	Color temperature:	4000 K
Color consistency: 3 SDCM	Color rendering index:	>90
	Color consistency:	3 SDCM

LIGHT SOURCE: 4 x LED 12.75W 1732lm

















NOTES

On request: DIM - UGR 19 For SUSPENSION version add KIT.

On request: Fabric power cord in two different colors:

cod.643000 (WHITE)

cod.613750 (BLACK). On request: DIAMOND PRISM screen for UGR&It;19 version.


BIG NEW 550 - DALI

5536N-LBN-DA





INDOOR > WALL - CEILING - SUSPENSION > BIG NEW

TECHNICAL DRAWING



PHOTOMETRIC CURVES





ACCESSORIES



Universal suspension Kit

980131 BR 980132 NE 980133 GR

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

