E6031-LBC-N

EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 175 KONIC EVO



FEATURES

| Intended Use: | Exteriors |
|-------------------|---|
| Installation: | Floor/Floor |
| Fixing: | Via pre-drilled holes for hardware (not included) |
| Body/Structure: | Extruded aluminum body and die-cast aluminum optical compartment |
| Painting: | Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorzirconing, epoxy powder primer and polyester powder surface finish). |
| Finish: | Anthracite gray |
| Reflector/Optics: | Die-cast conical reflector |
| Glass/Screen: | Transparent glass |
| Driver: | Integrated driver for LED, 500mA dc stabilized output |
| | |

TECHNICAL DATA

| Tension: | 220-240V 50/60Hz |
|------------------------|----------------------------------|
| Beam: | Omnidirectional symmetrical 360° |
| Current: | 500mA |
| Insulation class: | 2 |
| Weight: | 7 kg |
| IP grade: | 65 |
| Grade IK: | 10 |
| Glow wire: | 850 °C |
| Lamp included: | Yes |
| LED type: | SDM LED |
| Overall power: | 23 W |
| Appliance flow: | 842 lm |
| Nominal duration: | 50.000 (h) L90 B50 |
| Color temperature: | 3000 K |
| Color rendering index: | >90 |
| Color consistency: | 3 SDCM |

LIGHT SOURCE: 1 x 20W 2523.68Im



















NOTES


Maximum nighttime ambiance temperature when the fitting is on not exceeding 50°C Minimum nighttime ambiance temperature when the fitting is on not lower than -20 $^{\circ}\text{C}$ Maximum daytime ambiance temperature when the fitting is off not exceeding 60°C


EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 175 KONIC EVO

TECHNICAL DRAWING



PHOTOMETRIC CURVES





ACCESSORIES



Formwork for ground fixing

899-N

IP68 connector ø 7 to 12mm



646308 NE





646636 NE



VERSO 175 KONIC EVO - H.700mm - Omnidirectional

E6031-LBC-N



EXTERIOR > URBAN RESIDENTIAL BOLLARD > VERSO 175 KONIC EVO

Galvanized steel fixing plate with anchor belts

4074-N

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

