KE8140FMLBN40



EXTERIOR > WALKOVER MICRO RECESSED UPLIGHTERS > EYES GROUND







FEATURES

| Intended Use: | Exteriors |
|-------------------|--|
| Installation: | Ground recessed |
| Body/Structure: | Die-cast aluminum body EN AB-47100 - Stainless steel ring. |
| Painting: | Luminaire body base painted in polyester powder with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorzirconating, epoxy powder primer and polyester powder surface finish). |
| Finish: | Satin stainless steel |
| Reflector/Optics: | Metalized polycarbonate mirror reflector |
| Glass/Screen: | Clear tempered glass |
| Driver: | Remote driver for LED, 150mA dc stabilized output |

TECHNICAL DATA

| Tension: | 220-240V 50/60Hz |
|------------------------|---------------------------|
| Beam: | Symmetrical diffusing 40° |
| Current: | 150mA |
| Insulation class: | 5 |
| Weight: | 0.62 kg |
| IP grade: | 65 |
| Grade IK: | 7 |
| Drive-over: | Yes |
| Static load: | 500 kg |
| Glow wire: | 850 °C |
| Lamp included: | Yes |
| LED type: | COB LED |
| Overall power: | 6.2 W |
| Appliance flow: | 637 lm |
| Nominal duration: | 50.000 (h) L80 B23 |
| Color temperature: | 4000 K |
| Color rendering index: | >90 |
| Color consistency: | 3 SDCM |

LIGHT SOURCE: 1 x LED 6.10W 660Im















NOTES

Maximum nighttime ambiance temperature when the fitting is on not exceeding 50° C Minimum nighttime ambiance temperature when the fitting is on not lower than -20°C Maximum daytime ambiance temperature when the fitting is off not exceeding 60° C





EXTERIOR > WALKOVER MICRO RECESSED UPLIGHTERS > EYES GROUND

TECHNICAL DRAWING




PHOTOMETRIC CURVES






DRIVER




646209 DRIVER Remote driver x led



646397

Driver ON/OFF 6W 150mA IP68



645939 Driver DALI

DALI dimm. driver for led diodes, programmable output current, Pmax 26W



EYES 90 GROUND - KIT

KE8140FMLBN40



EXTERIOR > WALKOVER MICRO RECESSED UPLIGHTERS > EYES GROUND



646372-1

Driver KIT RGB 21W IP20 350mA

ACCESSORIES

EYES 90 ground formwork



185-C

Recessed formwork

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

