# **SMALL-BLADE LONG**

# E909BR-L-LBN

EXTERIOR > WALL STEP LIGHTING > SMALL-BLADE





#### **FEATURES**

| Intended Use:     | Exteriors   |
|-------------------|---|
| Installation:     | Wall Recessed   |
| Recessed hole:    | Recessed formwork type 503  |
| Fixing:           | Fastening system with hardware  |
| Body/Structure:   | Die-cast aluminum body EN AB-47100  |
| Painting:         | Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorzirconing, epoxy powder primer and polyester powder surface finish). |
| Finish:           | White   |
| Reflector/Optics: | LED lens in methacrylate  |
| Driver:           | Integrated driver for LED,<br>500mA dc stabilized output  |
|                   |   |

### TECHNICAL DATA

| Tension:               | 220-240V 50/60Hz  |
|------------------------|-------------------|
| Beam:                  | Asymmetrical      |
| Insulation class:      | 2                 |
| Weight:                | 1 kg              |
| IP grade:              | 67/68             |
| Glow wire:             | 850 °C            |
| Lamp included:         | Yes               |
| LED type:              | Power LED         |
| Overall power:         | 2 W               |
| Appliance flow:        | 66 lm             |
| Nominal duration:      | 50000 (h) L80 B10 |
| Color temperature:     | 4000 K            |
| Color rendering index: | >80               |
| Color consistency:     | 3 SDCM            |

LIGHT SOURCE: 1 x LED 2.00W 155Im







#### **NOTES**

ip grade referred to the light fixture only; power supply ip 67

Maximum nighttime ambiance temperature when the fitting is on not exceeding  $50^{\circ}$ C Minimum nighttime ambiance temperature when the fitting is on not lower than -20°C Maximum daytime ambiance temperature when the fitting is off not exceeding  $60^{\circ}$ C




# **SMALL-BLADE LONG**

# E909BR-L-LBN





EXTERIOR > WALL STEP LIGHTING > SMALL-BLADE

### **TECHNICAL DRAWING**



#### PHOTOMETRIC CURVES





### **COMPANY**

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

