## **BEND SLIM XL**

# 67306K-LBN-60

INDOOR > PROJECTORS & TRACKS 230V > BEND SLIM



## **FEATURES**

Installation: Track Mounting  Fixing: Electrical adapter for rail mounting  Body/Structure: Die-cast aluminum body EN AB-47100  Painting: Interior polyester powder coating  Finish: Black  Reflector/Optics: 99.8% pure aluminum reflector - Adjustable optics  Glass/Screen: Clear tempered glass  Driver: Driver: Driver built into the electrical adapter for track mounting, 1050mA stabilized output	Intended Use:	Interior
Body/Structure: Die-cast aluminum body EN AB-47100  Painting: Interior polyester powder coating  Finish: Black  Reflector/Optics: 99.8% pure aluminum reflector - Adjustable optics  Glass/Screen: Clear tempered glass  Driver: Driver: Driver built into the electrical adapter for track mounting,	Installation:	Track Mounting
Painting: Interior polyester powder coating  Finish: Black  Reflector/Optics: 99.8% pure aluminum reflector - Adjustable optics  Glass/Screen: Clear tempered glass  Driver: Driver: Driver built into the electrical adapter for track mounting,	Fixing:	Electrical adapter for rail mounting
Finish: Black  Reflector/Optics: 99.8% pure aluminum reflector - Adjustable optics  Glass/Screen: Clear tempered glass  Driver: Driver: Driver built into the electrical adapter for track mounting,	Body/Structure:	Die-cast aluminum body EN AB-47100
Reflector/Optics: 99.8% pure aluminum reflector - Adjustable optics  Glass/Screen: Clear tempered glass  Driver: Driver: Driver built into the electrical adapter for track mounting,	Painting:	Interior polyester powder coating
Glass/Screen: Clear tempered glass  Driver: Driver built into the electrical adapter for track mounting,	Finish:	Black
Driver: Driver built into the electrical adapter for track mounting,	Reflector/Optics:	99.8% pure aluminum reflector - Adjustable optics
Driver:	Glass/Screen:	Clear tempered glass
	Driver:	Driver built into the electrical adapter for track mounting, 1050mA stabilized output

#### **TECHNICAL DATA**

Tension:	220-240V 50/60Hz
Beam:	Symmetrical diffusing 60°
Current:	1050mA
Insulation class:	2
Weight:	1.9 kg
IP grade:	20
Glow wire:	850 °C
Lamp included:	Yes
LED type:	COB LED
Overall power:	41 W
Appliance flow:	4094 lm
Nominal duration:	50.000 ore L900 B20
Color temperature:	4000 K
Color rendering index:	> 90
Color consistency:	3 SDCM

LIGHT SOURCE: 1 x LED 37W 4870Im



















on request: 100mm base version for ceiling . on request: led with color temperature 2700k




## **BEND SLIM XL**


## 67306K-LBN-60


INDOOR > PROJECTORS & TRACKS 230V > BEND SLIM

### **TECHNICAL DRAWING**



#### PHOTOMETRIC CURVES





#### **COMPANY**

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.

