





FEATURES

Intended Use:	Interior	
Installation:	Ceiling Mounting	
Body/Structure:	Body made of extruded aluminum - Heads made of thermoplastic material	
Painting:	Interior polyester powder coating	
Finish:	White	
Reflector/Optics:	LED lens in methacrylate	
Glass/Screen:	Polycarbonate prismatic diffuser screen	
Driver:	Integrated driver for LED, 24Vdc output	

TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Symmetrical diffusing 120°
Current:	24Vdc
Insulation class:	1
Weight:	4.4 kg
IP grade:	40
Glow wire:	650 °C
Lamp included:	Yes
LED type:	SMD LED
Overall power:	48 W
Appliance flow:	4095 lm
Nominal duration:	50.000 (h) L80 B20
Color temperature:	4000 K
Color rendering index:	>90
Color consistency:	3 SDCM

LIGHT SOURCE: 2 x LED 22.00W 2900lm















NOTES





INDOOR > CONTROLLED LIGHT > TRAIL PLAFONE

TECHNICAL DRAWING

		2/ [
•	2060	34,5

PHOTOMETRIC CURVES





ACCESSORIES

3 phase track adapter



3193

Wall mount kit

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.