

## 68036LBC40-DA

INDOOR &gt; REMOVABLE-ADJUSTABLE RECESSED &gt; BEND XS ESTRAIBILE-ORIENTABILE



## FEATURES

Intended Use:	Interior
Installation:	Recessed Ceiling
Recessed hole:	Recess hole diam.125 mm. Ceiling thickness: 5-30 mm.
Fixing:	Steel springs
Body/Structure:	Die-cast aluminum body EN AB-47100
Painting:	Interior polyester powder coating
Finish:	Black
Reflector/Optics:	99.8% pure aluminum reflector - Removable and adjustable optics
Glass/Screen:	Clear tempered glass
Driver:	Integrated DALI dimmable driver for LEDs, max. output 700mA dc

## TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Symmetrical diffusing 40°
Current:	700mA
Insulation class:	2
Weight:	1.8 kg
IP grade:	20
Glow wire:	850 °C
Lamp included:	Yes
LED type:	COB LED
Overall power:	24 W
Appliance flow:	2629 lm
Nominal duration:	50.000 (h) L90 B20
Color temperature:	3000 K
Color rendering index:	> 90
Color consistency:	3 SDCM

LIGHT SOURCE: 1 x LED 24.00W 3180lm



## NOTES

