




FEATURES

| | |
|-----------------|--|
| Intended Use: | Interior |
| Installation: | Floor/wall/ceiling fixing |
| Fixing: | With brackets provided |
| Body/Structure: | Extruded aluminum body |
| Painting: | Anodized |
| Finish: | Anodized aluminum |
| Glass/Screen: | Polycarbonate diffuser screen |
| Driver: | Not included; must be ordered separately |

TECHNICAL DATA

| | |
|------------------------|----------------------------|
| Beam: | Symmetrical diffusing 100° |
| Insulation class: | 3 |
| Weight: | 0.40 kg |
| IP grade: | 40 |
| Glow wire: | 850 °C |
| Lamp included: | Yes |
| LED type: | SMD LED |
| Overall power: | 7.2 W |
| Appliance flow: | 489 lm |
| Nominal duration: | 25.000 (h) L80 B20 |
| Color temperature: | 5000 K |
| Color rendering index: | >90 |
| Color consistency: | 5 SDCM |

LIGHT SOURCE: 1 x LED 72.00W 6100lm




NOTES



l = 520mm

On request: 12Vdc

TECHNICAL DRAWING



PHOTOMETRIC CURVES



ACCESSORIES



Support for adjustable installation

130

COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.