



## FEATURES

Intended Use:	Exteriors,SIDESIGN
Installation:	Floor
Body/Structure:	Die-cast aluminum/stainless steel
Painting:	Powder coating with special outdoor pretreatment
Finish:	Inox
Reflector/Optics:	Methacrylate led lens
Glass/Screen:	Extra-clear crystal glass with silicone gaskets. Glass fixing ring and stainless steel shingle.
Driver:	Integrated

## TECHNICAL DATA


Tension:	220/240V
Beam:	Concentrating indirect light 15°
Current:	350mA
Insulation class:	3
Weight:	4.30 kg
IP grade:	IP67
Grade IK:	IK 10
Glow wire:	850° °C
Lamp included:	Yes
Overall power:	14.3 W
Appliance flow:	1040 lm
Nominal duration:	50.000 ore L80 B20
Color temperature:	3000 K
Color rendering index:	>90
Color consistency:	3 SDCM



## NOTES

IP68 connector (on request nc. 645230)

## TECHNICAL DRAWING



## COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.