

INDOOR > WALL - CEILING - SUSPENSION > STARGATE



FEATURES

| | |
|-----------------|---|
| Intended Use: | Interior |
| Installation: | Suspension |
| Fixing: | Suspension system with steel rope(s) L=3100 mm and micrometric adjustment |
| Body/Structure: | Sheet steel body |
| Painting: | Interior polyester powder coating |
| Finish: | Black |
| Glass/Screen: | Bi-satin polycarbonate diffuser screen |
| Driver: | Integrated driver for LED, 24Vdc output |

TECHNICAL DATA

| | |
|------------------------|----------------------------|
| Tension: | 220-240V 50/60Hz |
| Beam: | Symmetrical, dual emission |
| Insulation class: | 1 |
| Weight: | 70 kg |
| IP grade: | 40 |
| Glow wire: | 850 °C |
| Lamp included: | Yes |
| LED type: | Power LED |
| Overall power: | 192 W |
| Appliance flow: | 14018 lm |
| Nominal duration: | 50.000 ore L80 B10 |
| Color temperature: | 4000 K |
| Color rendering index: | > 80 |
| Color consistency: | 3 SDCM |

LIGHT SOURCE: 5 x LED 35.20W 4200lm



NOTES

suspension of the light fixture by means of 10 steel ropes.

Optional: Fabric power cord in two different colors:

cod.643000 (WHITE)

cod.613750 (BLACK)

TECHNICAL DRAWING



PHOTOMETRIC CURVES



COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.