



## FEATURES

Intended Use:	Exteriors
Installation:	Wall Mounting
Body/Structure:	Die-cast aluminum body EN AB-47100 - Stainless steel ring.
Painting:	Polyester powder coating with special outdoor treatment (sandblasting, pickling, No. 3 washing, fluorozirconing, epoxy powder primer and polyester powder surface finish).
Finish:	Grey
Reflector/Optics:	LED lens in methacrylate
Glass/Screen:	Clear screen-printed tempered glass
Driver:	Integrated driver for LED, 700mA dc stabilized output

## TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Symmetrical, dual emission 5 + 5°
Current:	700mA
Insulation class:	2
Weight:	2.9 kg
IP grade:	65
Glow wire:	850 °C
Lamp included:	Yes
LED type:	Power LED
Overall power:	6 W
Appliance flow:	209 lm
Nominal duration:	50.000 (h) L80 B20
Color temperature:	4000 K
Color rendering index:	>90
Color consistency:	3 SDCM

LIGHT SOURCE: 2 x LED 2.50W 135lm



## NOTES

Maximum nighttime ambient temperature when the fitting is on not exceeding 50°C  
 Minimum nighttime ambient temperature when the fitting is on not lower than -20°C  
 Maximum daytime ambient temperature when the fitting is off not exceeding 60°C

