



FEATURES

Intended Use:	Interior
Installation:	Ceiling/wall Mounting
Body/Structure:	EN AB-47100 die-cast aluminum body and sheet steel base
Painting:	Interior polyester powder coating
Finish:	Grey
Reflector/Optics:	99.8% pure aluminum reflector - Adjustable optics
Glass/Screen:	Transparent polycarbonate diffuser screen
Driver:	Integrated power supply for LED, stabilized output 150mA dc

TECHNICAL DATA

Tension:	220-240V 50/60Hz
Beam:	Concentric symmetrical 30°
Current:	150mA
Insulation class:	1
Weight:	1.8 kg
IP grade:	20
Glow wire:	650 °C
Lamp included:	Yes
LED type:	COB LED
Overall power:	20.8 W
Appliance flow:	2381 lm
Nominal duration:	50.000 (h) L90 B50
Color temperature:	3000 K
Color rendering index:	>90
Color consistency:	3 SDCM


LIGHT SOURCE: 4 x LED 5.20W 700lm





NOTES

On request: BEND MICRO SLIM for 3-phase track.
Photometry referred to single optical compartment

TECHNICAL DRAWING



PHOTOMETRIC CURVES



COMPANY

Side Spa has always been a benchmark in the manufacturing industry for its constant focus on product quality, assembly and sustainability of its items. The company is distinguished by its dedication to offering customers the highest quality products that meet needs and exceed expectations.

Side Spa pays the utmost attention to the quality of its products. Each stage of production undergoes rigorous quality control to ensure that only first-class items reach the market. By using high-quality materials and adopting state-of-the-art manufacturing processes, the company is able to offer products that stand the test of time and maintain their performance over the years. Quality is a top priority for Side Spa, which strives to meet the highest standards of excellence.